



Double cylinder 81.E15

with pulling- and highest drilling protection



Overview of Advantages

- Material: chrome nickel steel
- Standard length: 30/30 mm
- Chrome nickel steel web
- With hardened tumblers HRC60
- Drilling protection
- pulling protection
- Modular

Product description

- Double cylinder with Euro profile for mortise locks and surface-mounted locks of all types.

Scope of delivery

- 1 double cylinder
- 1 fixing screw, M5 × 85 mm

Product numbers

	8000 ²
Chrome nickel steel	81.E15

Optional Features

81.E15/30.0/E/30.0/A/A/50/--/50/--/SM

1	2	3	4	5	6	7	8	9	10	11	12
1: System	8 8000 ²										
2: Security level	E VdS BZ										
3: Length A	30 30 mm XX 5 mm increments										
4: Securitylevel A	E VdS BZ										
5: Length B	30 30 mm XX 5 mm increments										
6: Securitylevel B	A analog EN1303:2015-08; WD C E VdS BZ										
7: Corrosion protection	A EN1670-3 B increased corrosion protection										
8: Colour cover A	50 chrome-steel matt 57 gold decor 58 bronzed/light 59 chrome-plated black 60 chrome plated glossy										
9: Function A	-- none										
10: Colour cover B	50 chrome-steel matt 57 gold decor 58 bronzed/light 59 chrome-plated black 60 chrome plated glossy										
11: Function B	-- none										
12: Cam type	SM Standard position M SR Standard position R SL Standard position L SQ Standard position Q KM Eurokey position M MT Multilock MS Multilock narrow SP Spider gear wheel BL Biffar, left-hand BR Biffar, right-hand EM position EM SA Standard position A SB Standard position B SC Standard position C SD Standard position D NA Standard position A narrow NB Standard position B narrow NC Standard position C narrow ND Standard position D narrow NL Standard position L narrow										



Double cylinder 81.E15

with pulling- and highest drilling protection



NM Standard position M narrow
NQ Standard position Q narrow
NR Standard position R narrow
